

Boeing BMS 13-48 Extruded Cross-Linked ETFE  
BMS 13-48 Extruded Cross-Linked ETFE  
Aircraft Cable, Aerospace Cable

For other Boeing BMS Specs, click here

BMS 13-48 Extruded Cross-Linked ETFE Application:

General use in various areas of aircrafts

BMS 13-48 Extruded Cross-Linked ETFE Voltage Rating:

600 Volts



主称代号	线缆规格	Nom. Insul. Thick. (in)
BMS13-48T01	AWG Range of 10 to 24 with 1 to 5 Conductors	0.006
BMS13-48T02	AWG Range of 16 to 24 with 1 to 5 Conductors	0.006
BMS13-48T03	AWG Range of 10 to 24 with 1 to 5 Conductors	0.006
BMS13-48T04	AWG Range of 12 to 24 with 2 to 5 Conductors	0.006
BMS13-48T05	AWG Range of 16 to 24 with 1 to 5 Conductors	0.006
BMS13-48T06	AWG Range of 16 to 24 with 1 to 5 Conductors	0.006
BMS13-48T07	AWG Range of 16 to 24 with 2 to 5 Conductors	0.006
BMS13-48T08	AWG Range of 4/0 to 24 with 1 to 6 Conductors	0.01
BMS13-48T09	AWG Range of 16 to 24 with 1 to 6 Conductors	0.01
BMS13-48T10	AWG Range of 4/0 to 24 with 1 to 7 Conductors	0.008
BMS13-48T11	AWG Range of 16 to 24 with 1 to 6 Conductors	0.008
BMS13-48T12	AWG Range of 8 to 24 with 1 to 4 Conductors	0.008
BMS13-48T13	AWG Range of 16 to 24 with 1 to 6 Conductors	0.008
BMS13-48T14	AWG Range of 12 to 24 with 2 to 5 Conductors	0.008
BMS13-48T15	AWG Range of 12 to 24 with 1 to 4 Conductors	0.01
BMS13-48T16	AWG Range of 10 to 24 with 1 to 6 Conductors	0.015
BMS13-48T17	AWG Range of 12 to 24 with 2 to 5 Conductors	0.015
BMS13-48T18	AWG Range of 12 to 24 with 1 to 4 Conductors	0.015
BMS13-48T19	AWG Range of 16 to 24 with 1 to 6 Conductors	0.015
BMS13-48T20	AWG Range of 18 to 20 with 2 to 5 Conductors	0.015

BMS13-48T21	AWG Range of 18 to 20 with 1 to 4 Conductors	0.015
BMS13-48T22	AWG Range of 16 to 24 with 1 to 6 Conductors	0.015
BMS13-48T23	AWG Range of 16 to 24 with 1 to 6 Conductors	0.01
BMS13-48T24	AWG Range of 16 to 24 with 1 to 4 Conductors	0.01
BMS13-48T25	AWG Range of 12 to 24 with 1 to 5 Conductors	0.006
BMS13-48T26	AWG Range of 16 to 24 with 1 to 5 Conductors	0.006
BMS13-48T27	AWG Range of 12 to 24 with 1 to 4 Conductors	0.008
BMS13-48T28	AWG Range of 16 to 24 with 1 to 5 Conductors	0.008
BMS13-48T29	AWG Range of 16 to 24 with 1 to 5 Conductors	0.006
BMS13-48T30	AWG Range of 16 to 24 with 2 to 5 Conductors	0.006
BMS13-48T31	AWG Range of 16 to 24 with 1 to 6 Conductors	0.008
BMS13-48T32	AWG Range of 16 to 24 with 1 to 6 Conductors	0.008
BMS13-48T33	AWG Range of 18 to 24 with 2 to 5 Conductors	0.015
BMS13-48T34	AWG Range of 18 to 24 with 1 to 4 Conductors	0.015
BMS13-48T35	AWG Range of 12 to 24 with 1 to 6 Conductors	0.008
BMS13-48T36	AWG Range of 12 to 24 with 1 to 6 Conductors	0.006