

MIL-W-22759/3 | SAE AS22759/3
 MIL-W-22759/3 Wire (M22759/3 Wire)
 SAE AS22759/3
 MIL Spec Wire
 600V, 260°



MIL-W-22759/3 Wire (M22759/3 Wire) Description

Conductor: Nickel Plated Copper
 Insulation: PTFE, FEP, and Glass
 MIL-W-22759/3 Wire (M22759/3 Wire) Characteristics

Voltage Rating: 600 volts
 Temperature Rating: 260° C
 MIL-W-22759/3 Wire (M22759/3 Wire) Common Applications:

Durable Mil-W-22759/3 MIL-Spec Wire may be used in aircraft engines and other military, government, or civilian applications where abrasion Customization Services for MIL-W-22759/3 include:

Part Number	AWG Size	Conductor Stranding	Approx LBS/MFT	Min O.D. (in)	Max O.D. (in)
M22759/3-22	22	19/34	5.9	0.08	0.088
M22759/3-20	20	19/32	7.9	0.09	0.098
M22759/3-18	18	19/30	11	0.1	0.11
M22759/3-16	16	19/29	13.6	0.115	0.125
M22759/3-14	14	19/27	18.5	0.133	0.143
M22759/3-12	12	37/28	26.6	0.152	0.162
M22759/3-10	10	37/16	41.5	0.174	0.188
M22759/3-8	8	133/29	77.4	0.241	0.255
M22759/3-6	6	133/27	115	0.283	0.303
M22759/3-4	4	133/25	184	0.4	0.43
M22759/3-2	2	665/30	281	0.405	0.435
M22759/3-1	1	817/30	358	0.455	0.485
M22759/3-01	1/0	1045/30	436	0.495	0.535
M22759/3-02	2/0	1330/30	554	0.555	0.595