

MIL-W-22759/5 | SAE AS22759/5  
MIL-W-22759/5 Wire (M22759/5 Wire)  
SAE AS22759/5  
MIL Spec Wire  
600V, 200° C



MIL-W-22759/5 Wire (M22759/5 Wire) Description:

Conductor: Silver Plated Copper

Insulation: Extruded PTFE

MIL-W-22759/5 Wire (M22759/5 Wire) Characteristics:

Voltage Rating: 600 Volts

Temperature Rating: -55° C to +200° C

MIL-W-22759/5 Wire (M22759/5 Wire) Common Applications:

Mil-w-22759/5 wire may be used in aircraft engines and in other military, government, or civilian applications where abrasion is present.

\*Per specification, this product will have splices. If continuous lengths are needed, please ask.

Customization Services for MIL-W-22759/5 include:

Part Number	Nom. O.D. (in)	AWG Size	Conductor Stranding	Nom. Dia. of Cond.	Approx LBS/MFT
M22759/5-24	0.075	24	19/36	0.024	6
M22759/5-22	0.085	22	19/34	0.03	8
M22759/5-20	0.095	20	19/32	0.038	10
M22759/5-18	0.11	18	19/30	0.047	12.9
M22759/5-16	0.125	16	19/29	0.053	16.6
M22759/5-14	0.143	14	19/27	0.067	22.5
M22759/5-12	0.16	12	19/25	0.086	30.9
M22759/5-10	0.18	10	37/26	0.108	42.5
M22759/5-8	0.248	8	133/29	0.162	77